

NIPPON WEATHERBOND ALGAEGUARD

DESCRIPTION	:	Nippon Weatherbond AlgaeGuard is a long lasting high performance water-based acrylic exterior paint specially formulated with enhanced anti-algae and anti-streak marks performance.
TYPE	:	100% acrylic emulsion for exterior use
COLOUR	:	Wide range of colours
FINISH	:	Low Sheen
USES	:	Suitable for new and previously painted surfaces such as masonry, bricks and exterior timber.
FEATURES	:	<ul style="list-style-type: none">• Enhanced resistance to fungal and algal growth• Enhanced anti-streak marks property keeping the façade clean• Excellent weather durability under local climatic conditions• Good adhesion on stable surfaces• Easy application with good levelling property• Excellent anti-carbonation property• High water vapour permeability• Environmentally friendly paint certified under the Singapore Green Labeling Scheme SGL-032 by the Singapore Environment Council with V.O.C. level less than 50g/L

APPLICATION DATA

METHOD	:	Roller or brush
THEORETICAL COVERAGE	:	Approx. 9 m ² / litre (based on 40 microns DFT)
DILUTION	:	Ready for use, if necessary, dilution should not be more than 5% water.
SURFACE PREPARATION	:	Ensure surface is clean, dry and stable. Remove loose surface matter and contaminants by appropriate means. Treat fungus growth areas with NIPPON ANTI-FUNGUS SOLUTION.

NIPPON WEATHERBOND ALGAEGUARD

DRYING TIME	:	Surface Dry - 30 minutes at 30 °C Hard Dry - 1 hour at 30 °C
OVERCOATING TIME	:	2 hours based on normal conditions
RECOMMENDED PAINTING SYSTEM	:	1 coat of Nippon Vinilex 2000 Wall Sealer, or Nippon Vinilex 5170 Wall Sealer 2 coats of Nippon Weatherbond AlgaeGuard
CLEANING	:	All equipment should be cleaned with water immediately after use.
GENERAL INFORMATION		
SOLID CONTENT	:	55.0 ± 2% by weight (based on white colour)
SPECIFIC GRAVITY	:	1.35 ± 2% (based on white colour)
PACKING	:	1- litre, 5-litre and 20-litre
STORAGE	:	Store in a tightly sealed container in a cool dry
SHELF LIFE	place. :	Up to 18 months in a tightly sealed container.
PRECAUTION	:	Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment. Refer to the product Safety Data Sheet for more information.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details : **Nippon Paint Lanka (Pvt) Ltd.**
Nippolac Towers,
69A, Buthgamuwa Road,
Rajagiriya,
Sri Lanka.
Phone +94-114-600400
Fax +94-112-866751
E-mail: colombo@nipponpaint.com.lk
Web : www.nipponpaint.lk