

DESCRIPTION	A rapid drying concentrated stain with high penetrating power designed for spraying or brush application. It has excellent grain raising. Ideal for furniture, kitchen cupboards, wall panels, doors and windows. It colours the wood to bring it as near as possible to the final desired colour of the Wood Finish system.
TYPE	Solvent based wood stain.
COLOUR	Jak wood, Teak, Mahogany ,Walnut, Ebony, Red Wood, Rose wood and Deep Mahogany
USES	Recommended for application on wood surfaces prior to the use of sanding sealer or with Sanding sealer (This depends on the application method & coating system)
FEATURES	Quick drying penetrating stain.
APPLICATION DATA	
METHOD	Brush, Spray, Rag, Dip
THINNING	Nippolac Furniture Thinner
SURFACE PREPARATION	Eliminate oil, water, grit, dirt, marking paints and any other foreign matter.
APPLICATION	The wood stain must be thoroughly stirred and applied to the surface by brush or cloth pad. Allow to stain for a few minutes before removing the excess by wiping along the grain with a clean cloth pad. The removal of all excess stain is essential to ensure good adhesion of subsequent coating. Different colour densities can be obtained by varying the intensity of wiping.
DRYING TIME	10 Minutes at 30 °C ± 2 °C and RH 65 % ± 5%



TECHNICAL DATA SHEET FOR

NIPPOLAC WOODSTAIN

CLEANING All equipment should be cleaned with Nippolac Furniture Thinner immediately after use.

GENERAL INFORMATION

FLASH POINT 21 °C

SOLID CONTENT 2.50 ± 0.10% by weight

CONSISTANCY Ready to use

DILUTION Usually no Thinning is required. Thinning can be used to lighten tone.

SPECIFIC GRAVITY Appr. 0.842

PACKING 250 ml, 500ml, 1 ltr, 4 lts

SHELF LIFE Up to 5 years in a tightly sealed container

STORAGE Store in secure dry conditions inaccessible to children and animals. Containers should be kept tightly closed during storage. Avoid spillage and contamination. Do not empty into drains or water courses.

PRECAUTIONS Avoid contact with skin and eyes and inhalation of vapours. Use in good natural ventilation and wear protective clothing. Wear suitable respiratory protection when applying. Exclude sources of ignition during application and drying. No smoking.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice

Enquiries Contacts :

Nippon Paint Lanka (Pvt) Ltd.
Nippolac Towers,
69A, Buthgamuwa Road, Rajagiriya,
Sri Lanka.
Phone +94-114-600400
Fax +94-114-600409
E-mail: colombo@nipponpaint.lk
Web : www.nipponpaint.lk