

DESCRIPTION	Nippolac Acrylic wall filler is for interior plastered surfaces or painted walls with outstanding filling properties. It will hide the surface imperfections and help obtain a smooth high quality finish. It will minimize the absorption and save the cost of the first coat of paint
TYPE	Vinyl acetate ethylene co-polymer emulsion based primer
FINISH	Matt
COLOUR	White
USES	It is suitable for all normal interior masonry surfaces including brickwork, plaster, cement, asbestos and wallboard
FEATURES	Excellent filling properties Hides surface imperfections Minimizes the top coat application
APPLICATION DATA	
METHOD	Roller , brush,
THEORETICAL COVERAGE	10-15 Sq.m / liter This will depend on the surface texture.
DILUTION	Maximum up to 20 % with clean water
SURFACE PREPARATION	<p>The substrate must be clean and free from loose particles, dirt, grease and traces of foreign material. For loose plaster areas, remove the defective materials and re-plaster the area.</p> <p>Suggested surface treatment</p> <ol style="list-style-type: none">Dirt/Powder High-pressure water wash. Clean with damp cloth (internal). Mild detergent may be used.Paint Unstable old film to be removed by high –pressure wash or scraper whichever is appropriate.Plaster Remove with chisel, scraper, powder grinder etc. Replace towards a stable surface with an approved mortar mixture.Moisture High moisture causes paint defect. Observe the following levels prior to



TECHNICAL DATA SHEET FOR
NIPPOLAC ACRYLIC WALL FILLER

painting :

-Masonry- below 12 %

-All water seepage must be checked

v. Fungus

Remove by high –pressure jet wash and treat with NIPPON ANTI-FUNGUS SOLUTION. Rinse again with clean water and dry.

vi. Oil / Grease

Clean off with a mild detergent and a little solvent. Wash thoroughly to remove all traces.

DRYING TIME

Surface drying 15 minutes at 30 °C ± 2 °C and RH 65 % ± 5%

Hard Dry 2-4 hours at 30 °C ± 2 °C and RH 65 % ± 5%

CLEANING

All equipment should be cleaned with water immediately after use.

GENERAL INFORMATION

SOLID CONTENT

61 % by weight

DENSITY

1.55 kg/litre

PACKING

1 ltr, 4 ltr, 10ltr , 20 ltr & 200 ltr

STORAGE

Store in a tightly sealed container in a cool dry place.

SHELF LIFE

Up to 5 years in a tightly sealed container

PRECAUTIONS

Keep away from food. Avoid contact with eyes & sensitive skin. In case of contact, wash with running water. Use appropriate protective equipment & provide ample ventilation during application. Keep the product out of reach of children.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice

Enquiries Contacts :

Nippon Paint Lanka (Pvt) Ltd.

Nippolac Towers,

69A, Buthgamuwa Road,

Rajagiriya,

Sri Lanka.

Phone +94-114-600400

Fax +94-114-600409



TECHNICAL DATA SHEET FOR
NIPPOLAC ACRYLIC WALL FILLER

E-mail: colombo@nipponpaint.com.lk

Web : www.nipponpaint.lk