



TECHNICAL DATA SHEET FOR
NIPPOLAC ROAD MARKING PAINT - ADVANCE

DESCRIPTION	Nippolac Road Marking paint is a quick-drying, high abrasion resistant, durable coating recommended for high traffic conditions on Traffic Lines, Pedestrian Crossings, Pavement edgings, brick surfaces, streets, highways, bridges, tunnels and curbing. It could be used separately or bound with reflective beads. Reflective glass beads are dropped onto the surface before the paint dries to form the reflectorized paint.	
TYPE	Acrylic	
COLOUR	White, Yellow and Black.	
USES	Traffic Lines, Pedestrian Crossings, Pavement edgings and curbing	
FEATURES	Excellent adhesion and abrasion resistance	
APPLICATION DATA		
METHOD	Roller , brush, spray (special gun)	
THEORETICAL COVERAGE	6 – 8 Sq. m / ltr This will highly depend on the surface texture. The actual coverage will depend on the surface texture	
SURFACE PREPARATION	Eliminate mil – scale, oil, water, dirt, grease and any foreign matter. The undercoat should be dry.	
DRYING TIME	Touch drying	15 minutes at 30 °C ± 2 °C and RH 65 % ± 5%
	Dry (no-pick-up)	1 Hour at 30 °C ± 2 °C and RH 65 % ± 5%
	Hard Dry	16 Hours at 30 °C ± 2 °C and RH 65 % ± 5%
APPLICATION DETAILS	Stir well before use. Can be applied with brush or special spray equipment. This paint is reflectorized by dropping beads onto the wet paint. Any suitable dispensing equipment can be used provided the glass beads are uniformly spread on the surface at the specified rate. Avoid any kind of fire during the application.	
CLEANING	All equipment should be cleaned with Nippolac Rainbow Thinner immediately after use.	



TECHNICAL DATA SHEET FOR
NIPPOLAC ROAD MARKING PAINT - ADVANCE

GENERAL INFORMATION

SOLID CONTENT	57± 3 %
FLASH POINT	29 °C
CONSISTANCY	Ready to use
THINING	Nippolac Rainbow Thinner
SPECIFIC GRAVITY	Appr. 1.3
PACKING	1 ltr, 4 ltr, 200ltr
STORAGE	Store in a tightly sealed container in a cool dry place.
SHELF LIFE	Up to 5 years in a tightly sealed container
PRECAUTIONS	Flammable ; do not expose to heat of flame. Avoid direct contact with skin. Provide ample ventilation during paint application. Wear eye protectors and disposable respirators. Keep the product out of reach of children.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice

Enquiries Contacts :

Nippon Paint Lanka (Pvt) Ltd.
Nippolac Towers,
69A, Buthgamuwa Road,
Rajagiriya,
Sri Lanka.
Phone +94-114-356900
Fax +94-114-356909
E-mail: colombo@nipponpaint.com.lk
Web : www.nipponpaint.lk