

<b>DESCRIPTION</b>	A water based wood putty designed to fill holes, splits & cracks in timber, MDF & other wood related substrates. Characterized by its excellent low sink back & non shrink properties.
<b>TYPE</b>	Water based Wood Putty
<b>COLOUR</b>	Teak, Mahogany , Jack wood, Walnut, Rosewood, Natural
<b>USES</b>	Ideally suited for all types of soft and hard woods, inside and outside.
<b>FEATURES</b>	Non Shrinking property Excellent filling property Easy to apply & sand down

### **APPLICATION DATA**

**SURFACE PREPARATION** Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. The moisture level of the substrate should be below 12 %

**APPLICATION** Apply wood putty by a stainless steel spatula on all timber & composite board defects. For example, holes, cracks and splits.  
If defects are deep, fill in two or three applications to avoid cracking of the putty due to stress caused by shrinkage. Select a lighter shade putty colour than the timber when intending to apply stain as to avoid pronounced repair marks. Sand to a smooth finish using #180 grade abrasive paper.

**SUITABLE TOPCOATS** Nippolac N.C. / Water based wood coatings systems

**DRYING TIME**

Surface drying	45 minutes at 30 °C ± 2 °C and RH 65 % ± 5%
Recoating	16 hours at 30 °C ± 2 °C and RH 65 % ± 5%
Hard Dry	24 hours at 30 °C ± 2 °C and RH 65 % ± 5%

(The drying time depends on the application thickness )



TECHNICAL DATA SHEET FOR  
**NIPPOLAC WOOD PUTTY**

**CLEANING**

All equipment should be cleaned with clean water immediately after use.

**GENERAL INFORMATION**

**FLASH POINT**

N/A

**SOLID CONTENT**

85 % ± 5%

**CONSISTENCY**

Ready to use

**SPECIFIC GRAVITY**

Appr. 1.75

**PACKING**

100g, 175g, 500g, 1 kg, 2 kg

**STORAGE**

Store in a tightly sealed container in a cool dry place.

**SHELF LIFE**

Up to 5 years in a tightly sealed container

**STORAGE**

Store in secure dry conditions inaccessible to children and animals. Containers should be kept tightly closed during storage. Do not empty into drains or water courses.

**PRECAUTIONS**

Avoid contact with sensitive skin and eyes. Use appropriate protective equipment.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice

**Enquiries Contacts :**

Nippon Paint Lanka (Pvt) Ltd.  
Nippolac Towers,  
69A, Buthgamuwa Road, Rajagiriya,  
Sri Lanka.  
Phone +94-114-600400  
Fax +94-114-600409  
E-mail: [colombo@nipponpaint.lk](mailto:colombo@nipponpaint.lk)  
Web : [www.nipponpaint.lk](http://www.nipponpaint.lk)