



## TECHNICAL DATA SHEET FOR NIPPON WATER BASED FLOOR PAINT

DESCRIPTION	Nippon water based floor paint is 100% acrylic coating specially designed for use on properly prepared interior and exterior floors, porches and other cementitious surfaces. Its smooth, low sheen finish provides excellent weather resistance, hardness and durability which resists fading and peeling off. It applies easily, is an environmentally friendly with excellent coverage. Nippon water based floor paint can be applied to well prepared, previously painted surfaces.		
TYPE	Acrylic Emulsion		
COLOUR	Red, Green, Grey, Brown, Black		
FINISH	Low sheen		
USES	It is suitable for use on properly prepared interior and exterior floors, porches and other cementitious surfaces and also may be applied to well prepared, previously painted surfaces.		
FEATURES	Low sheen emulsion Fungi resistant Excellent Abrasion Resistance		
APPLICATION DATA			
METHOD	Roller, brush, air and airless spray		
THEORETICAL COVERAGE	8 - 10 m <sup>2</sup> /liter at wet film thickness of 90 microns (DFT 40 microns) (Based on white colour). <i>* The Actual coverage will depend on the surface texture.</i>		
DILUTION	Maximum 5% with clean water		
SURFACE PREPARATION	Should be swept clean of dirt and loose particles. Grease should be removed by washing with a diluted soap solution. Then wash the surface off thoroughly with clean water. Smooth concrete should be treated with Nippon Etching solution then wash off with clean water before application of Nippolac Water Based Floor paint.		
DRYING TIME	Touch Dry	30 minutes at 30 °C ± 2 °C and RH 65 % ± 5%	
	Hard Dry	24 hour at 30 °C ± 2 °C and RH 65 % ± 5%	
OVERCOATING TIME	4 hours minimum based on normal conditions		
RECOMMENDED PAINTING SYSTEM	2 coats of Nippon water Based floor paint		



## TECHNICAL DATA SHEET FOR NIPPON WATER BASED FLOOR PAINT

### CLEANING

All equipment should be cleaned with water immediately after use.

### GENERAL INFORMATION

#### SOLID CONTENT

53.0 ± 2.% by weight (Based on white colour)

#### SPECIFIC GRAVITY

1.1-1.2 ± 0.10 (Based on white colour)

#### PACKING

1 ltr, 4 ltr, 10ltr

#### SHELF LIFE

Up to 5 years in a tightly sealed container

#### STORAGE

Store in secure dry conditions inaccessible to children and animals.  
Containers should be kept tightly closed during storage.  
Avoid spillage and contamination.  
Do not empty into drains or water courses.  
The remaining paint should be kept in a properly sealed container.

### PRECAUTIONS

Ensure good ventilation during application and drying of paint.  
Avoid direct contact with sensitive skin.  
Use appropriate personal protective equipment.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

### Enquiries Contacts:

Nippon Paint Lanka (Pvt) Ltd.  
69A, Buthgamuwa Road,  
Rajagiriya,  
Sri Lanka.  
Phone +94-114-600400  
Fax +94-114-600409  
E-mail: [info@nipponpaint.com.lk](mailto:info@nipponpaint.com.lk)  
Web : [www.nipponpaint.lk](http://www.nipponpaint.lk)