

NIPPON ODOUR-LESS BRILLIANT WHITE**DESCRIPTION**

Odour-Less Brilliant White is specially formulated to have extremely low odour for interior use and making it a safer paint for your family and environment with improve indoor air quality.

With the “Green” ingredients, it limits air pollutants and other environmental impacts. Hence, it is especially ideal for use in eco-sensitive commercial and residential areas with high frequency human traffic such as hospitals, schools, residential buildings and hotels.

TYPE : Modified Acrylic Polymer Emulsion for interior use

COLOUR : White

FINISH : Classic Matt finish

USES :

- Premium green coating for protection of internal masonry surfaces, such as cement, plastered walls, brickwork and fibre boards.
- Ideal for use on interior walls of hospitals, schools, offices and residential buildings

FEATURES :

- Low VOC
- Low Odour
- Excellent flow
- Excellent coverage
- Provides a durable, washable film
- Fungus & mould resistant
- Non-toxic and lead, mercury and heavy metals free

APPLICATION DATA

METHOD : Roller or brush

THEORETICAL COVERAGE : Theoretical 15 - 17 m² / litre (35 microns DFT) Actual coverage will depend on the surface texture and application method.

DILUTION :

Dilute with clean water as follows:

- : Brush - 25% max
- : Roller - 25% max

NIPPON ODOUR-LESS BRILLIANT WHITE**SURFACE PREPARATION**

Ensure surface is clean, dry and stable using the following suggested surface treatments:

- **Moisture:** There must not be any water residue on the surface of the substrate. Moisture must be 12% before application
- **Unstable matter:** Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable
- **Contaminants:** Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry
- **Fungus and Algae:** Wash the affected area to remove unstable matters and micro-organisms. Apply Anti-Fungus Solution and leave on for at least 2 hours
- **Hairline cracks :** Fill cracks with suitable exterior grade water-resistant putty or filler

DRYING TIME : Surface Dry - 30 minutes at 30 °C
Hard Dry - 2 hour at 30 °C

OVERCOATING TIME : 2 hours minimum based on normal conditions

RECOMMENDED PAINTING SYSTEM :

- 1 coat Vinilex 2000 wall Sealer
- 2 coats Odour-Less Brilliant White

CLEANING : All equipment should be cleaned with water immediately after use.

GENERAL INFORMATION

SOLID CONTENT : 56 ± 2.0 % by weight

SPECIFIC GRAVITY : 1.40 ± 2.0 % kg/litre

PACKING : 1 litre and 5 litres

STORAGE : Store in a tightly sealed container in a cool dry place.

SHELF LIFE : Up to 24 months in a tightly sealed container.

PRECAUTION : Ensure good ventilation during application and drying of paint.
Avoid direct contact with sensitive skin.
Use appropriate personal protective equipment.
Refer to the product Safety Data Sheet for more information.



TECHNICAL DATA SHEET FOR

NIPPON ODOUR-LESS BRILLIANT WHITE

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details:

Nippon Paint Lanka (Pvt) Ltd.
Nippolac Towers,
69A, Buthgamuwa Road,
Rajagiriya,
Sri Lanka.
Phone +94-114-600400
Fax +94-112-866751
E-mail: colombo@nipponpaint.com.lk
Web : www.nipponpaint.lk