

TECHNICAL DATA SHEET FOR
NIPPOLAC WOOD PRESERVATIVE CLEAR

DESCRIPTION	A non-staining, clear, Phenolic- based, quick -drying wood preserver containing effective insecticide & fungicide. Provides deep protection to wood against all types of moulds, mildew and other fungi and destroys the termites & wood boring insects. It penetrates to preserve.
TYPE	Wood preservatives
COLOUR	Pale Amber
USES	Recommended for application on wood surfaces prior to painting or varnishing.
FEATURES	Quick -drying wood preserver containing effective insecticide & fungicide.
APPLICATION DATA	
METHOD	Roller , brush, Spray
THEORETICAL COVERAGE	10 - 12 m ² /liter (Coverage depends on the surface texture & wood type)
CONSISTENCY	Ready for use
DILUTION	Dilution not recommended
SURFACE PREPARATION	Eliminate oil, water, grit, dirt, marking paints and any foreign matter.
MOISTURE CONTENT	Below 12 %
DRYING TIME	Drying 4 -6 Hours at 30 °C ± 2 °C and RH 65 % ± 5%
CLEANING	All equipment should be cleaned with Nippolac Turpentine immediately after use.
TOP COATS	Sanding sealers ,Varnishes, Water based wood care, Wood finish Lacquer.



TECHNICAL DATA SHEET FOR
NIPPOLAC WOOD PRESERVATIVE CLEAR

GENERAL INFORMATION

FLASH POINT	38 °C
CONSISTANCY	Ready to use
SPECIFIC GRAVITY	Appr. 0.75 ± 0.5
PACKING	625 ml, 2 ltr, 4 ltr, 10ltr, 200 ltr
SHELF LIFE	Up to 5 years in a tightly sealed container
STORAGE	Store in secure dry conditions inaccessible to children and animals. Containers should be kept tightly closed during storage. Avoid spillage and contamination. Do not empty into drains or water courses.

PRECAUTIONS

Avoid contact with skin and eyes and inhalation of vapours. Use in good natural ventilation and wear protective clothing. Wear suitable respiratory protection when applying. Exclude sources of ignition during application and drying. No smoking.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice

Enquiries Contacts :

Nippon Paint Lanka (Pvt) Ltd.
Nippolac Towers,
69A, Buthgamuwa Road,
Rajagiriya,
Sri Lanka.
Phone +94-114-600400
Fax +94-112-866751
E-mail: colombo@nipponpaint.lk
Web : www.nipponpaint.lk