



TECHNICAL DATA SHEET FOR

NIPPON WATER BASED PRESERVATIVE WOOD STAIN

DESCRIPTION	Nippon water-based wood stain has good flow property, ideal blocking action against tannin, oozing and it protects and enhances the beauty of wood work and furniture with a quick and easy application. It has high penetrating power designed for spraying or brush application. It has excellent resistance to fading and grain raising. Ideal for furniture, kitchen cupboards, wall panels, doors and windows (both interior & exterior).
TYPE	Water based wood stain.
COLOUR	Larch Teak , Burma Teak, Natural Mahogany , Natural Walnut
USES	Ideal for furniture, kitchen cupboards, wall panels, doors and windows (both interior & exterior).
FEATURES	Excellent penetrating property Recommended for both interior & exterior use. Fine resistance to fading Excellent grain raising. DIY product. Containing effective insecticide & fungicide
APPLICATION DATA	
METHOD	Brush, Spray
THINNING	Ready for use. 150-160 ft ² /Lt (Coverage highly depend on the type of wood and application types)
SURFACE PREPARATION	Eliminate oil, water, grit, dirt, marking paints and any other foreign matter. The moisture level of the substrate should be below 12 %
APPLICATION	Sand with P 80, P120, P180 grit sand papers & clean. Proper surface preparation gives best results. To lighten the color, wipe off with a soft cloth soon after applying & allow complete drying before over coating. The final colour depends on type, absorption & colour of the original timber. Allow complete drying before over coating. To darken the color, Increase the number of coats. Stir well before use.



TECHNICAL DATA SHEET FOR

NIPPON WATER BASED PRESERVATIVE WOOD STAIN

DRYING TIME	30 minutes at 30 °C ± 2 °C and RH 65 % ± 5%
SANDABILITY	3-4 Hours
RECOMMENDED TOPCOAT	Nippolac Water based wood lacquer
CLEANING	All equipment should be cleaned with clean water immediately after use.

GENERAL INFORMATION

FLASH POINT	N/A
SOLID CONTENT	10.30 ± 0.10% by weight
SPECIFIC GRAVITY	Appr. 0.310
CONSISTANCY	Ready for use
SPECIFIC GRAVITY	Appr. 1.02
PACKING	4 lts. , 1 ltr, 500 ml,
SHELF LIFE	Up to 2 years in a tightly sealed container
STORAGE	Store in secure dry conditions inaccessible to children and animals. Containers should be kept tightly closed during storage. Avoid spillage and contamination. Do not empty into drains or water courses. The remaining paint should be kept in a properly sealed container.
PRECAUTIONS	Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice

Enquiries Contacts :

Nippon Paint Lanka (Pvt) Ltd.
Nippolac Towers,
69A, Buthgamuwa Road, Rajagiriya,
Sri Lanka.
Phone +94-114-600400
Fax +94-114-600409
E-mail: colombo@nipponpaint.lk
Web : www.nipponpaint.lk