



TECHNICAL DATA SHEET FOR  
NIPPOLAC FLOOR PAINT (Q/D)

<b>DESCRIPTION</b>	Nippolac quick drying floor paint is recommended for interior dry cement, concrete or wooden floors. It provides a durable decorative gloss finish with excellent drying & abrasion resistance properties.	
<b>TYPE</b>	Long oil alkyd gloss finish containing polyurethane	
<b>FINISH</b>	Gloss	
<b>COLOUR</b>	Grey, Green, Red, Brown, Black	
<b>USES</b>	Recommended for painting interior cement surfaces.	
<b>FEATURES</b>	Excellent filling & levelling properties Fast drying Fine Gloss level, durability, adhesion & abrasion resistance.	
<b>APPLICATION DATA</b>		
<b>METHOD</b>	Roller , brush, Spray	
<b>THEORETICAL COVERAGE</b>	10 – 11 m <sup>2</sup> /liter at dry film thickness of 40 microns The Actual coverage will depend on the surface texture	
<b>DILUTION</b>	Use Nippolac Mineral Turpentine 10 % max	
<b>SURFACE PREPARATION</b>	Eliminate oil, water, dirt, grease , any other loose paints & any other foreign matter. The Surface should be thoroughly dry (The moisture content should be less than 8 %) & Cement floors should preferably incorporate a damp-proof membrane.	
<b>DRYING TIME</b>	Touch dry	1 Hour at 30 °C ± 2 °C and RH 65 % ± 5%
	Hard Dry	24 Hours at 30 °C ± 2 °C and RH 65 % ± 5%
	Overcoat	16 Hours at 30 °C ± 2 °C and RH 65 % ± 5%
<b>APPLICATION DETAILS</b>	Stir well before use. Avoid excessive thinning. Provide adequate ventilation. Do not apply on rainy days or in wet conditions.	



TECHNICAL DATA SHEET FOR  
NIPPOLAC FLOOR PAINT (Q/D)

**CLEANING** All equipment should be cleaned with Nippolac mineral turpentine immediately after use.

**GENERAL INFORMATION**

**SOLID CONTENT** 70 ± 2 % by mass

**FLASH POINT** 35 °C

**CONSISTANCY** Ready to use

**THINING** Nippolac Mineral Turpentine max 10 %

**SPECIFIC GRAVITY** 1.00 ± 0.10

**PACKING** 200 ml, 500 ml, 1 ltr, 2 ltr, 4 ltr, & 200 ltr

**SHELF LIFE** Up to 5 years in a tightly sealed container

**STORAGE** Store in secure dry conditions inaccessible to children and animals. Containers should be kept tightly closed during storage. Avoid spillage and contamination. Do not empty into drains or water courses.

**PRECAUTIONS** Avoid contact with skin and eyes and inhalation of vapours. Use in good natural ventilation and wear protective clothing. Wear suitable respiratory protection when applying. Exclude sources of ignition during application and drying. No smoking.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice

**Enquiries Contacts :**

Nippon Paint Lanka (Pvt) Ltd.  
Nippolac Towers,  
69A, Buthgamuwa Road,  
Rajagiriya,  
Sri Lanka.  
Phone +94-114-356900  
Fax +94-114-356909  
E-mail: colombo@nipponpaint.com.lk  
Web : www.nipponpaint.lk