



TECHNICAL DATA SHEET FOR  
**NIPPOLAC NITROCELLULOSE SANDING SEALER (CLEAR / STAINED )**

<b>DESCRIPTION</b>	Nippolac N.C. Sanding Sealer is a nitro-cellulose based sealer with excellent filling & sanding properties. It seals the surface and on flattening with abrasive paper after the appropriate drying time, forms a smooth surface coating to which the topcoat may be applied. It has excellent durability and good adhesion with fast drying properties. It prevents excess absorption of top coat and enhances the beauty of wood.
<b>TYPE</b>	Nitrocellulose- based sanding sealer
<b>COLOUR</b>	Clear / Stained
<b>USES</b>	Nippolac sanding sealer is a fine base coat for Nippolac wood finishes and Polyurethane varnishes. It is suitable for interior wooden furniture, wall panelling, office desks, chairs , cabinets and, pantry cupboards. It has excellent sandability and wood grain filling properties.
<b>FEATURES</b>	Quick drying Easy to sand Excellent filling properties
<b>APPLICATION DATA</b>	
<b>METHOD</b>	Brush, Spray
<b>THINNING</b>	Nippolac Furniture Thinner  Brush Application : 1 part of Sanding Sealer to 2 parts of Nippolac Furniture Thinner. Add 10% Retarder when painting is done by brush application or when the weather is very humid.  Spray Method : 1 part of Sanding Sealer to 3 parts of Nippolac Furniture Thinner.
<b>SURFACE PREPARATION</b>	Eliminate oil, water, grit, dirt, marking paints and any other foreign matter. The moisture level of the substrate should be below 12 %
<b>APPLICATION</b>	Can be sprayed or applied with brush. Due to fast drying properties, take precautions to prevent the increase in thickness.



TECHNICAL DATA SHEET FOR

**NIPPOLAC NITROCELLULOSE SANDING SEALER (CLEAR / STAINED )**

<b>SUITABLE TOPCOAT</b>	Nippolac NC wood finish or Nippolac polyurethane varnish.
<b>DRYING TIME</b>	Surface drying 15 minutes at 30 °C ± 2 °C and RH 65 % ± 5% Recoating 2 hours at 30 °C ± 2 °C and RH 65 % ± 5% Hard Dry 16 hours at 30 °C ± 2 °C and RH 65 % ± 5%
<b>CLEANING</b>	All equipment should be cleaned with Nippolac Furniture Thinner immediately after use.
<b>GENERAL INFORMATION</b>	
<b>FLASH POINT</b>	18 °C
<b>SOLID CONTENT</b>	62.10 ± 0.10 % by weight
<b>SPECIFIC GRAVITY</b>	Appr. 1.864
<b>PACKING</b>	200ml, 500ml, 1lt , 4lt and 5 ltr
<b>SHELF LIFE</b>	Up to 5 years in a tightly sealed container
<b>STORAGE</b>	Store in secure dry conditions inaccessible to children and animals. Containers should be kept tightly closed during storage. Avoid spillage and contamination. Do not empty into drains or water courses.
<b>PRECAUTIONS</b>	Provide ample ventilation during application & sanding. Wear eye protectors and disposable respirators. Avoid contact with eyes & sensitive skin. In case of contact, wash with running water. Exclude sources of ignition during application and drying. No smoking.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice

**Enquiries Contacts :**

Nippon Paint Lanka (Pvt) Ltd.  
Nippolac Towers,  
69A, Buthgamuwa Road,  
Rajagiriya,  
Sri Lanka.  
Phone +94-114-600400  
Fax +94-114-600409  
E-mail: colombo@nipponpaint.com.lk  
Web : www.nipponpaint.lk