

DESCRIPTION	Nippolac Exterior Acrylic wall filler is a fungus resistant acrylic primer for newly plastered surfaces or painted walls , plywood, MDF ceilings with outstanding filling properties. Hides surface imperfections and helps obtain a smooth high quality finish for both interior & exterior surfaces. It minimizes the absorption and saves the cost of the first coat of paint.
TYPE	Styrene acrylic co-polymer Emulsion based filler
FINISH	Matt
COLOUR	White
USES	It is suitable for all normal interior or exterior masonry surfaces including brickwork, plaster, cement, asbestos and wallboards.
FEATURES	Excellent filling properties Hides surface imperfections Fungus resistant
APPLICATION DATA	
METHOD	Roller , brush,
THEORETICAL COVERAGE	10 – 15 Sq.m / liter at dry film thickness 35 microns. The actual coverage will depend on the surface texture.
DILUTION	Maximum up to 20 % with clean water
SURFACE PREPARATION	The substrate must be clean and free from loose particles, dirt, grease and traces of foreign material. For loose plaster areas, remove the defective materials and re-plaster the area. Suggested surface treatment <ol style="list-style-type: none">1. Dirt/Powder High-pressure water (external) wash. Clean with damp cloth (internal). Mild detergent may be used.2. Paint Unstable old film to be removed by high –pressure wash , white sand paper or scraper whichever is appropriate.3. Plaster Remove with chisel, scraper, powder grinder etc. Replace towards a stable surface with an approved mortar mixture.



TECHNICAL DATA SHEET FOR
NIPPOLAC EXTERIOR ACRYLIC WALL FILLER

4. Moisture

High moisture causes paint defects. Observe the following level prior to painting

- Masonry- below 12 %
- All water seepage must be checked

5. Fungus

Remove by high –pressure jet wash and treated with NIPPON ANTI-FUNGUS SOLUTION. Rinse again with clean water and dry.

6. Oil / Grease

Clean off with a mild detergent and a little solvent. Wash thoroughly to remove all traces.

DRYING TIME

Surface drying 15 - 20 minutes at 30 °C ± 2 °C and RH 65 % ± 5%
Hard Dry 2-4 hours at 30 °C ± 2 °C and RH 65 % ± 5%

CLEANING

All equipment should be cleaned with water immediately after use.

GENERAL INFORMATION

SOLID CONTENT

60 - 65 % by weight

DENSITY

1.58 ± 0.05 kg/litre

PACKING

1 ltr, 4 ltr, 10ltr , 20 ltr & 200 ltr

STORAGE

Store in a tightly sealed container in a cool dry place.

SHELF LIFE

Up to 5 years in a tightly sealed container

PRECAUTIONS

Keep away from food. Avoid contact with eyes & sensitive skin. In case of contact, wash with running water. Use appropriate protective equipment & provide ample ventilation during application. Keep the product out of reach of children.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice

Enquiries Contacts :

Nippon Paint Lanka (Pvt) Ltd.
Nippolac Towers,
69A, Buthgamuwa Road,
Rajagiriya,
Sri Lanka.



TECHNICAL DATA SHEET FOR
NIPPOLAC EXTERIOR ACRYLIC WALL FILLER

Phone +94-114-600400
Fax +94-114-600409
E-mail: colombo@nipponpaint.lk
Web : www.nipponpaint.lk