



TECHNICAL DATA SHEET FOR  
**NIPPON SUPER GLOSS ENAMEL**

<b>DESCRIPTION</b>	It is a fast drying, tough, high gloss Enamel paint with durability, brushability, levelling and filling properties. Recommended for painting on wood, steel and cement on most interior and exterior surfaces.
<b>TYPE</b>	Air drying long oil alkyd gloss finish
<b>FINISH</b>	Gloss finish
<b>COLOUR</b>	As per the colour card
<b>USES</b>	Recommended for painting on wood, steel and cement on most interior and exterior surfaces.
<b>FEATURES</b>	Excellent filling & levelling properties Fine durability , brushability

**APPLICATION DATA**

<b>METHOD</b>	Roller , brush, Spray
<b>THEORETICAL COVERAGE</b>	15 - 16 m <sup>2</sup> /liter at dry film thickness of 40 microns The actual coverage will depend on the surface texture
<b>SURFACE PREPARATION</b>	Eliminate mil – scale, oil, water, dirt, Grease and any foreign matter. The undercoats should be thoroughly dry.
<b>DILUTION</b>	Use Nippon Mineral Turpentine 10 % max
<b>DRYING TIME</b>	Touch dry      3 -4 Hours at 30 °C ± 2 °C and RH 65 % ± 5% Hard Dry      24 Hours at 30 °C ± 2 °C and RH 65 % ± 5% Overcoat      16 Hours at 30 °C ± 2 °C and RH 65 % ± 5%
<b>APPLICATION DETAILS</b>	Stir well before use. Avoid excessive thinning. Provide adequate ventilation.
<b>SUITABLE UNDERCOATS</b>	Nippolac Aluminium wood primer for wood surfaces. Nippolac Zn Phosphate Metal Primers or Nippolac Anticorrosive paint for Metal Surfaces.



TECHNICAL DATA SHEET FOR  
**NIPPON SUPER GLOSS ENAMEL**

**CLEANING** All equipment should be cleaned with Nippon Mineral Turpentine immediately after use.

**GENERAL INFORMATION**

**SOLID CONTENT** 65.0 ± 2.% by weight (Based on white colour)

**FLASH POINT** 34 °C

**CONSISTANCY** Ready to use

**THINING** Nippolac Mineral Turpentine  
Max 10 %

**SPECIFIC GRAVITY** 1.35 ± 0.10 (Based on white colour)

**PACKING** 200 ml, 500 ml, 2 ltr , 1 ltr, 4 ltr, & 200 ltr

**SHELF LIFE** Up to 5 years in a tightly sealed container

**STORAGE** Store in secure dry conditions inaccessible to children and animals. Containers should be kept tightly closed during storage. Avoid spillage and contamination. Do not empty into drains or water courses.

**PRECAUTIONS** Avoid contact with skin and eyes and inhalation of vapors. Use in good natural ventilation and wear protective clothing. Wear suitable respiratory protection when applying. Exclude sources of ignition during application and drying. No smoking.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice

**Enquiries Contacts :**

Nippon Paint Lanka (Pvt) Ltd.  
Nippolac Towers,  
69A, Buthgamuwa Road, Rajagiriya,  
Sri Lanka.  
Phone +94-114-600400  
Fax +94-114-600409  
E-mail: colombo@nipponpaint.lk  
Web : www.nipponpaint.lk